

MANTA EVO HP

Packaged water/water reversible heat pumps for indoor installation.

Cooling Capacity: 21 ÷ 457 kW

Heating Capacity: 26 ÷ 550 kW



Hydraulic connections on the top side

Low noise

Single or double refrigerant circuit

Scroll compressors

Plate type heat exchangers


EER up to 4,30

COP up to 4,11

ESEER up to 5,89



MANTA EVO HP: Packaged water cooled heat pumps for indoor installation, equipped with fully hermetic scroll compressors, plate type evaporator and condenser.
Cooling Capacity: $21 \div 457 \text{ kW}$
Heating Capacity: $26 \div 550 \text{ kW}$



MANTA EVO HP



MAIN FEATURES

- Water cooled heat pump.
- 22 models, 2 versions available, for a wide selection opportunity.
- Average step of 20kW.
- EER up to 4,30.
- COP up to 4,11.
- ESEER up to 5,89.
- Scroll compressors.
- R410A Refrigerant charge.
- Plate type heat exchangers.
- Suitable for indoor installation.

MAIN BENEFITS

- New frame, more compact, suitable to walks in through a standard door;
- Hydraulic connections on the top side of the machine;
- Reduction of service spare around the machine;
- New control software, developed by RC Group, with an advanced control logic;
- Increased cooling density, up to 210kW per m²;
- Increased heating density, up to 250kW per m²;
- Total front access for the routine maintenance;
- Up to two compressors for each refrigerant circuit to reach a high efficiency.
- Units with single or double refrigerant circuits.
- Low sound level guaranteed by the cabinet structure;
- Availability of plant side and source side pumping groups.
- Availability of partial heat recovery system.
- Easily of maintenance.
- Eurovent Certification.
- Up to A++ Class. ErP 2015.

INDOOR INSTALLATION

The machines are designed for indoor installation.

REDUCED NOISE EMISSION

The machines are characterized by a low sound level guaranteed by the containing structure.

NEW FRAME, MORE COMPACT

Suitable to walks in through a standard door

HYDRAULIC CONNECTION ON THE TOP SIDE OF THE MACHINE

DOMESTIC HOT WATER

On request is possible to install the system for the domestic hot water production.

WORKING LIMITS IN COOLING MODE

Evaporator chilled water outlet temperature: $-12 \div 20^{\circ}\text{C}$
Condenser outlet water temperature: $20 \div 60^{\circ}\text{C}$

MAIN COMPONENTS

FRAMEWORK

- Base in aluminium extrusion, painted with epoxy powders. Colour RAL 9005;
- Supporting feet in galvanized steel sheet with holes for floor fixing or rubber shock absorbers installation;
- Inner frame and upper frame in aluminium profile, painted with epoxy powders. The inner frame is provided with seals for the panels. Colour RAL 9005;
- Panels in galvanized steel sheet with protective surfaces treatment in compliance with UNI ISO 9227/ASTMB117 and ISO 7253, and painted with epoxy powders. Colour RAL 7016 hammered;
- Removable frontal panels for a total front access for routine maintenance;
- Removable side panels with grilles for interior ventilation;
- Compartment for electrical panel on unit front for direct access to control and regulation devices;
- Hydraulic connections on the machine top cover.

COMPRESSORS

- Orbiting spiral (SCROLL) hermetic compressors with spiral profile optimized for R410A refrigerant;
- ON / OFF capacity control (0 / 100% each compressor);
- 2-pole 3-phase electric motor with direct on line starting;
- Crankcase heater;
- Electric motor thermal protection via internal winding temperature sensors;
- Equalization system of the lubricant oil for units equipped with 2 or 3 compressors operating on the same refrigerating circuit;
- Rubber supports.

PLANT SIDE HEAT EXCHANGER

- AISI 316 stainless steel plates type, vacuum brazed using copper as brazing material. Hydraulic and refrigerant connections in AISI 316 stainless steel:
 - With single hydraulic circuit for all machines;
 - With single refrigerant circuit for S version machines;
 - With double refrigerant circuit for D version machines.
- Polyurethane insulation foam with closed cell;
- Temperature sensors on water inlet and outlet;
- Factory assembled differential water pressure switch for water flow control;
- Hydraulic piping insulated with closed cell elastomeric foam;
- Hydraulic connections on the machine top cover.

EXHAUSTION SIDE HEAT EXCHANGER

- AISI 316 stainless steel plates type, vacuum brazed using copper as brazing material. Hydraulic and refrigerant connections in AISI 316 stainless steel:
 - With single hydraulic circuit for all machines;
 - With single refrigerant circuit for S version machines;
 - With double refrigerant circuit for D version machines.
- 0÷10V proportional signal to manage the motorized valve for the condensing control (summer working mode) and evaporating control (winter working mode).
- Polyurethane insulation foam with closed cell;
- Temperature sensor on water outlet;
- Hydraulic piping insulated with closed cell elastomeric foam;
- Hydraulic connections on the machine top cover.

REFRIGERANT CIRCUIT

Components for each refrigerant circuit:

- Reversing valve for refrigeration cycle inversion
- Thermostatic expansion valve;
- Electronic expansion valve for models 236 P2 S – 284 P4 D - 280 P3 S – 328 P4 D - 354 P3 S – 372 P4 D – 422 – P4 D - 472 P4 D;
- Sight glass;
- Electromagnetic valve on liquid line. The valve is not installed on models 236 P2 S – 284 P4 D - 280 P3 S – 328 P4 D - 354 P3 S – 372 P4 D – 422 – P4 D - 472 P4 D;
- Filter dryer on liquid line;
- Service valve on liquid line upstream the filter dryer. The valve is present only with exchangeable cartridge filter;
- Safety valves on high and low pressure side;
- Pressure transducers with indication, control and protection functions, on low and high refrigerant pressure;
- High pressure safety switch with manual reset;
- Refrigerant circuit with copper tubing with insulation of the suction line;
- Plastic capillary hoses for pressure sensors connection;
- R410A refrigerant charge.

ELECTRICAL PANEL

In accordance with EN60204-1 norms, suitable for indoor installation, complete with:

- Main switch with door lock safety on frontal panel;
- Magnetothermic switches or fuses for each compressor;
- Contactors for each compressor motor;
- Transformer for auxiliary circuit and microprocessor supply;
- Machine operating mode selector "Loc – Off - Remote":
 - Loc position: Machine is active;
 - Off position: Machine is deactivated;
 - Remote position: The machine is remotely controlled with a command by the Customer. Electric connections in the terminal.
- Machine operating mode selector "Summer – Winter - Remote":
 - Summer position: Summer working mode with chilled water production.
 - Winter position: Winter working mode with hot water production.
 - Remote position: The machine is remotely controlled with a command by the Customer. Electric connections in the terminal.

• Terminals:

OUTLETS

- Voltage free deviating contact for General Alarm 1.
- Voltage free deviating contact for General Alarm 2 – only for units with single refrigerant circuit.

INLETS

- External enabling (from timer, ecc. At Customer care);
- Remote control (from operating mode selector. At Customer care); Emergency unit stop with signalling on display (external alarm. At Customer care).;
- Panel with machine controls;
- Power supply: 400V / 3Ph / 50Hz.

OUTLETS

- Voltage free deviating contact for General Alarm 1.
- Voltage free deviating contact for General Alarm 2 – only for units with single refrigerant circuit.

INLETS

- External enabling (from timer, ecc. At Customer care);
- Remote control (from operating mode selector. At Customer care);
- Emergency unit stop with signalling on display (external alarm. At Customer care).;
- Panel with machine controls;
- Power supply: 400V / 3Ph / 50Hz.

CONTROL SYSTEM

Microprocessor control system with graphic display for control and monitor of operating and alarms status. The system includes:

- Built-in clock for alarms date and time displaying and storing;
- Built-in memory for the storing of the intervened events (up to 100 events recorded);
- Predisposition for connectivity board housing (RCcom MBUS/JBUS, LON, BACnet for Ethernet (SNMP- TCP/IP), BACnet for MS/TP). The electronic cards are optional accessories;
- Main components hour-meter;
- Non-volatile "Flash" memory for data storage in case of power supply faulty;
- Analogue set point compensation (0÷10 Vdc) according to an external analogue signal at Customer care;
- Menu with protection password;
- LAN connection (max 15 units).

OPTIONAL ACCESSORIES

MANTA EVO HP	22 P1	30 P1	37 P1	44 P1	40 P2	50 P2	60 P2	72 P2	88 P2	114 P2	142 P2	186 P2
SIZE	S M1	S M1	S M1	S M1	S M2	S M2	S M2	S M2	S M2	S M3	S M3	S M3
739 - Pumping group (plant side)	•	•	•	•	•	•	•	•	•	•	•	-
Pumping group (source side)	•	•	•	•	•	•	•	•	•	•	•	-
960 - Free contact enable plant pump	•	•	•	•	•	•	•	•	•	•	•	-
Free contact enable source pump	•	•	•	•	•	•	•	•	•	•	•	-
752 - Hydronic group (1 pump)	•	•	•	•	•	•	•	•	•	•	•	•
753 - Hydronic group (2 pumps)	•	•	•	•	•	•	•	•	•	•	•	•
764 - Water tank	•	•	•	•	•	•	•	•	•	•	•	•
1004 - Antifreezing heater for pumping group	•	•	•	•	•	•	•	•	•	•	•	•
780 - Noise absorption box	•	•	•	•	•	•	•	•	•	•	•	•
610 - Noise deadening cup on compressor	•	•	•	•	•	•	•	•	•	•	•	•
171 - Rubber antivibration holders (kit)	•	•	•	•	•	•	•	•	•	•	•	•
118 - Kit brine A (for glycol solution production up to -6°C)	•	•	•	•	•	•	•	•	•	•	•	•
119 - Kit brine B (for glycol solution production up to -12°C)	•	•	•	•	•	•	•	•	•	•	•	•
460 - Kit for outdoor installation	•	•	•	•	•	•	•	•	•	•	•	•
450 - Partial heat recovery	•	•	•	•	•	•	•	•	•	•	•	•
449 - Voltage free contact for partial heat recovery water pump activation	•	•	•	•	•	•	•	•	•	•	•	•
785 - Sanitary antifreezing heater	•	•	•	•	•	•	•	•	•	•	•	•
1023 - Double circuit version	-	-	-	-	•	•	•	•	•	•	•	•
605 - Compr. power factor capacitor - 0,9	•	•	•	•	•	•	•	•	•	•	•	•
1002 - Soft Starter	•	•	•	•	•	•	•	•	•	•	•	•
83 - Compressor operation indicator	•	•	•	•	•	•	•	•	•	•	•	•
220 - Electronic expansion valve	•	•	•	•	•	•	•	•	•	•	•	•
Electronic Expansion valve energy reserve module	•	•	•	•	•	•	•	•	•	•	•	•
552 - Service valves on compressor	•	•	•	•	•	•	•	•	•	•	•	•
Ambient temperature sensor	•	•	•	•	•	•	•	•	•	•	•	•
85 - Demand limit	•	•	•	•	•	•	•	•	•	•	•	•
81 - Phases sequence control	•	•	•	•	•	•	•	•	•	•	•	•
651 - Special power supply 230/3/50 Hz	-	•	•	•	-	•	•	•	•	•	-	-
1003 - Analogic flowmeter	•	•	•	•	•	•	•	•	•	•	•	•
1005 - Power supply analyzer	•	•	•	•	•	•	•	•	•	•	•	•
1009 - Multimeter kit	•	•	•	•	•	•	•	•	•	•	•	•
84 - Additional external alarm	•	•	•	•	•	•	•	•	•	•	•	•
923 - RC-Com MBUS/JBUS Serial board	•	•	•	•	•	•	•	•	•	•	•	•
926 - LON Serial board	•	•	•	•	•	•	•	•	•	•	•	•
931 - BACnet Ethernet - SNMP - TCP/IP Serial board	•	•	•	•	•	•	•	•	•	•	•	•
932 - BACnet MS/TP Serial board	•	•	•	•	•	•	•	•	•	•	•	•
930 - Remote graphic terminal kit	•	•	•	•	•	•	•	•	•	•	•	•
962 - Kit modem GSM	•	•	•	•	•	•	•	•	•	•	•	•
957 - Plantwatch without modem	•	•	•	•	•	•	•	•	•	•	•	•
889 - Master plant SEQUENCER	•	•	•	•	•	•	•	•	•	•	•	•
RC CLOUD PLATFORM	•	•	•	•	•	•	•	•	•	•	•	•

• available accessory; - not available accessory

OPTIONAL ACCESSORIES

MANTA EVO HP	211 P2	236 P2	148 P4	176 P4	228 P4	284 P4	328 P4	372 P4	422 P4	472 P4
SIZE	S	S	D	D	D	D	D	D	D	D
	M3	M3	M4	M4	M4	M4	M4	M4	M4	M4
739 - Pumping group (plant side)	-	-	-	-	-	-	-	-	-	-
Pumping group (source side)	-	-	-	-	-	-	-	-	-	-
960 - Free contact enable plant pump	-	-	-	-	-	-	-	-	-	-
Free contact enable source pump	-	-	-	-	-	-	-	-	-	-
752 - Hydronic group (1 pump)	•	•	•	•	•	•	•	•	•	•
753 - Hydronic group (2 pumps)	•	•	•	•	•	•	•	•	•	-
764 - Water tank	•	•	•	•	•	•	•	•	•	•
1004 - Antifreezing heater for pumping group	•	•	•	•	•	•	•	•	•	•
780 - Noise absorption box	•	•	•	•	•	•	•	•	•	•
610 - Noise deadening cup on compressor	•	•	•	•	•	•	•	•	•	•
171 - Rubber antivibration holders (kit)	•	•	•	•	•	•	•	•	•	•
118 - Kit brine A (for glycol solution production up to -6°C)	•	•	•	•	•	•	•	•	•	•
119 - Kit brine B (for glycol solution production up to -12°C)	•	•	•	•	•	•	•	•	•	•
460 - Kit for outdoor installation	•	•	•	•	•	•	•	•	•	•
450 - Partial heat recovery	•	•	•	•	•	•	•	•	•	•
449 - Voltage free contact for partial heat recovery water pump activation	•	•	•	•	•	•	•	•	•	•
785 - Sanitary antifreezing heater	•	•	•	•	•	•	•	•	•	•
1023 - Double circuit version	•	•	-	-	-	-	-	-	-	-
605 - Compr. power factor capacitor - 0,9	•	•	•	•	•	•	•	•	•	•
1002 - Soft Starter	•	•	•	•	•	•	•	•	•	•
83 - Compressor operation indicator	•	•	•	•	•	•	•	•	•	•
220 - Electronic expansion valve	•	-	•	•	•	•	•	•	•	-
Electronic Expansion valve energy reserve module	•	-	•	•	•	•	•	•	•	-
552 - Service valves on compressor	•	•	•	•	•	•	•	•	•	•
Ambient temperature sensor	•	•	•	•	•	•	•	•	•	•
85 - Demand limit	•	•	•	•	•	•	•	•	•	•
81 - Phases sequence control	•	•	•	•	•	•	•	•	•	•
651 - Special power supply 230/3/50 Hz	-	-	•	•	•	-	-	-	-	-
1003 - Analogic flowmeter	•	•	•	•	•	•	•	•	•	•
1005 - Power supply analyzer	•	•	•	•	•	•	•	•	•	•
1009 - Multimeter kit	•	•	•	•	•	•	•	•	•	•
84 - Additional external alarm	•	•	•	•	•	•	•	•	•	•
923 - RC-Com MBUS/JBUS Serial board	•	•	•	•	•	•	•	•	•	•
926 - LON Serial board	•	•	•	•	•	•	•	•	•	•
931 - BACnet Ethernet - SNMP - TCP/IP Serial board	•	•	•	•	•	•	•	•	•	•
932 - BACnet MS/TP Serial board	•	•	•	•	•	•	•	•	•	•
930 - Remote graphic terminal kit	•	•	•	•	•	•	•	•	•	•
962 - Kit modem GSM	•	•	•	•	•	•	•	•	•	•
957 - Plantwatch without modem	•	•	•	•	•	•	•	•	•	•
889 - Master plant SEQUENCER	•	•	•	•	•	•	•	•	•	•
RC CLOUD PLATFORM	•	•	•	•	•	•	•	•	•	•

• available accessory; - not available accessory

TECHNICAL DATA MANTA EVO HP

MANTA EVO HP		22 P1	30 P1	37 P1	44 P1	40 P2	50 P2	60 P2	72 P2
SIZE		S M1	S M1	S M1	S M1	S M2	S M2	S M2	S M2
Seasonal energy efficiency class (*)		ErP A+	A++	A++	A++	A++	A++	A++	A++
Summer working mode - Cooling capacity (1) kW		21	29	37	43	39	49	59	73
Unit power input	kW	5,5	7,2	9,0	10,8	9,8	12,2	14,0	18,4
Plant exchanger water flow rate	m³/h	3,6	4,9	6,4	7,4	6,7	8,4	10,1	12,4
Plant exchanger pressure drop	kPa	33	30	38	27	22	33	29	33
Exhaust exchanger water flow rate	m³/h	4,5	6,2	7,9	9,2	8,4	10,5	12,5	15,6
Exhaust exchanger pressure drop	kPa	49	45	57	42	30	28	29	45
Winter working mode - Heating capacity (2) kW		26	35	44	52	47	60	70	86
Unit power input	kW	7,1	9,3	11,6	13,7	12,5	15,7	18,0	23,0
Plant exchanger water flow rate	m³/h	3,6	4,9	6,4	7,4	6,7	8,4	10,1	12,4
Plant exchanger pressure drop	kPa	56	50	67	49	20	30	26	30
Exhaust exchanger water flow rate	m³/h	3,3	4,5	5,7	6,7	6,0	7,6	9,1	11,0
Exhaust exchanger pressure drop	kPa	27	25	30	22	18	19	19	27
STANDARD	Compressors	scroll	scroll	scroll	scroll	scroll	scroll	scroll	scroll
	Quantity	n.	1	1	1	2	2	2	2
	Capacity steps	n.	1	1	1	2	2	2	2
	Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A	R410A
	Total refrigerant charge (optional excluded)	kg	1,4	2,3	2,4	3,0	2,4	5,1	5,4
	Gas circuits	n.	1	1	1	1	1	1	1
	Power supply	V/Ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
	Max unit operating current (FLA)	A	17	23	33	36	32	44	65
	Unit starting current (LRA)	A	101	139	140	174	116	146	171
	EER (1)	kW/kW	3,80	3,99	4,09	3,96	3,97	4,01	3,94
OPTION	COP (2)	kW/kW	3,64	3,76	3,80	3,80	3,78	3,80	3,74
	ESEER		4,07	4,39	4,34	5,26	5,26	4,40	5,07
	Sound power level [Lw] (3)	dB(A)	66,7	68,7	70,7	71,7	70,0	72,0	74,0
	Average sound pressure level [Lp _m] (4)	dB(A)	51,0	53,0	55,0	56,0	54,0	56,0	58,0
	Net weight	kg	225	251	267	278	338	385	401
	Hydraulic connections								
	Plant / Exhaust exchanger IN/OUT - ISO228/1-G M Ø		1+1/2"	1+1/2"	1+1/2"	1+1/2"	--	--	--
	Plant / Exhaust exchanger IN/OUT - OD (5)	Ø mm	--	--	--	--	60,3	60,3	60,3
	Partial heat recovery (6)								
	Heating capacity	kW	3,0	4,1	5,2	6,0	5,5	6,9	10,0
OPTION	Pumping group								
	Plant side - Power input	kW	0,75	0,55	0,90	0,90	0,75	0,75	1,10
	Source side - Power input	kW	0,75	0,55	0,90	0,90	0,75	1,10	1,10
	Water tank - volume	l	250	250	250	250	250	250	250

1. Referred to chilled water temperature 12/7°C – 0% glycol solution; water temperature to the condenser 30/35°C – 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.
2. Referred to hot water outlet temperature at 45°C and chilled water temperature 15/10°C - 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.
3. Sound power level [Lw] according to ISO EN 9614 - 2
4. Average sound pressure level [Lp_m] 1m far according to ISO EN 3744.
5. Hydraulic connection with grooved end complete with flexible joint and adapter pipe for solder connection.
6. Referred to chilled water temperature 12/7°C – 0% glycol solution; water temperature to the condenser 30/35°C – 0% glycol solution; water temperature heat recovery 40/45°C – 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.

(*) **ErP** Seasonal energy efficiency class according to energy label directive 2010/30/EU and EU regulations 811/2013.


TECHNICAL DATA MANTA EVO HP

MANTA EVO HP		88 P2	114 P2	142 P2	186 P2	211 P2	236 P2	148 P4	176 P4
SIZE		S M2	S M3	S M3	S M3	S M3	S M3	D M4	D M4
Seasonal energy efficiency class (*)	ErP	A++	A++	A++	A++	A++	A++	A++	A++
Summer working mode - Cooling capacity (1) kW		86	110	138	180	204	226	152	175
Unit power input	kW	21,4	27,3	34,3	43,9	50,5	57,7	35,3	42,8
Plant exchanger water flow rate	m³/h	14,7	18,9	23,6	30,9	35	38,8	26,1	30
Plant exchanger pressure drop	kPa	25	37	34	31	33	36	28	36
Exhaust exchanger water flow rate	m³/h	18,4	23,6	29,6	38,5	43,7	48,8	32,1	37,4
Exhaust exchanger pressure drop	kPa	26	34	36	41	47	48	37	37
Winter working mode - Heating capacity (2) kW		105	139	174	225	246	283	179	209
Unit power input	kW	27,4	34,6	43,1	54,7	61,3	70,4	45,1	53,5
Plant exchanger water flow rate	m³/h	14,7	18,9	23,6	30,9	35,0	38,8	26,1	30,0
Plant exchanger pressure drop	kPa	34	41	38	36	30	43	47	45
Exhaust exchanger water flow rate	m³/h	13,4	18,2	22,7	29,6	32,0	36,9	23,3	27,0
Exhaust exchanger pressure drop	kPa	12	21	22	24	30	27	23	31
Compressors		scroll	scroll	scroll	scroll	scroll	scroll	scroll	scroll
Quantity	n.	2	2	2	2	2	2	4	4
Capacity steps	n.	2	2	2	2	2	2	4	4
Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Total refrigerant charge (optional excluded)	kg	6,2	8,7	11,4	12,7	13,8	14,6	14,3	15,6
Gas circuits	n.	1	1	1	1	1	1	2	2
Power supply	V/Ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
Max unit operating current (FLA)	A	71	84	102	137	155	173	130	143
Unit starting current (LRA)	A	208	265	320	375	473	490	233	276
EER (1)	kW/kW	4,01	4,03	4,02	4,10	4,04	3,92	4,30	4,09
COP (2)	kW/kW	3,83	4,02	4,04	4,11	4,01	4,02	3,97	3,91
ESEER		5,47	5,18	5,19	5,32	5,21	5,09	5,81	5,89
Sound power level [Lw] (3)	dB(A)	75,0	80,6	83,6	83,6	86,1	87,6	78,2	79,2
Average sound pressure level [L _{pm}] (4)	dB(A)	59,0	64,0	67,0	67,0	69,5	71,0	61,0	62,0
Net weight	kg	412	696	732	798	835	871	1024	1034
Hydraulic connections									
Plant / Exhaust exchanger IN/OUT - ISO228/1-G M Ø	--	--	--	--	--	--	--	--	--
Plant / Exhaust exchanger IN/OUT - OD (5)	Ø mm	60,3	76,1	76,1	88,9	88,9	88,9	88,9	88,9
Partial heat recovery (6)									
Heating capacity	kW	12,1	16,5	20,6	26,8	29,0	33,4	21,1	24,5
Pumping group									
Plant side - Power input	kW	1,10	1,85	1,85	--	--	--	--	--
Source side - Power input	kW	1,85	1,85	1,85	--	--	--	--	--
Water tank - volume	l	250	380	380	380	380	380	380	380

1. Referred to chilled water temperature 12/7°C – 0% glycol solution; water temperature to the condenser 30/35°C – 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.
2. Referred to hot water outlet temperature at 45°C and chilled water temperature 15/10°C - 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.
3. Sound power level [Lw] according to ISO EN 9614 - 2
4. Average sound pressure level [L_{pm}] 1m far according to ISO EN 3744.
5. Hydraulic connection with grooved end complete with flexible joint and adapter pipe for solder connection.
6. Referred to chilled water temperature 12/7°C – 0% glycol solution; water temperature to the condenser 30/35°C – 0% glycol solution; water temperature heat recovery 40/45°C – 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.

(*) ErP Seasonal energy efficiency class according to energy label directive 2010/30/EU and EU regulations 811/2013.

TECHNICAL DATA MANTA EVO HP


MANTA EVO HP		228 P4	284 P4	328 P4	372 P4	422 P4	472 P4
SIZE		D M4	D M4	D M4	D M4	D M4	D M4
STANDARD	Seasonal energy efficiency class (*)	 A++	A++	A++	A++	A++	A++
	Summer working mode - Cooling capacity (1) kW	222	279	320	359	406	457
	Unit power input	kW	54,5	68,9	78,6	87,8	100,5
	Plant exchanger water flow rate	m³/h	38,2	47,9	55	61,6	69,8
	Plant exchanger pressure drop	kPa	41	44	41	50	39
	Exhaust exchanger water flow rate	m³/h	47,6	59,7	68,6	76,8	87,3
	Exhaust exchanger pressure drop	kPa	43	55	51	48	33
	Winter working mode - Heating capacity (2) kW	267	336	386	433	489	550
	Unit power input	kW	68,8	87,0	99,2	111,6	126,4
	Plant exchanger water flow rate	m³/h	38,2	47,9	55,0	61,6	69,8
	Plant exchanger pressure drop	kPa	56	88	68	74	46
	Exhaust exchanger water flow rate	m³/h	34,3	43,2	49,6	55,7	62,8
	Exhaust exchanger pressure drop	kPa	35	27	28	31	29
	Compressors	scroll	scroll	scroll	scroll	scroll	scroll
	Quantity	n.	4	4	4	4	4
	Capacity steps	n.	4	4	4	4	4
	Refrigerant	R410A	R410A	R410A	R410A	R410A	R410A
	Total refrigerant charge (optional excluded)	kg	20,5	26,2	28,4	30,6	34,1
	Gas circuits	n.	2	2	2	2	2
	Power supply	V/Ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
	Max unit operating current (FLA)	A	168	204	239	275	311
	Unit starting current (LRA)	A	345	416	471	505	620
	EER (1)	kW/kW	4,07	4,05	4,07	4,09	4,04
	COP (2)	kW/kW	3,88	3,86	3,89	3,88	3,87
	ESEER		5,59	5,49	5,60	5,59	5,65
	Sound power level [Lw] (3)	dB(A)	84,2	87,2	87,2	87,2	89,7
	Average sound pressure level [Lp _m] (4)	dB(A)	67,0	70,0	70,0	70,0	72,5
	Net weight	kg	1384	1507	1538	1558	1692
OPTION	Hydraulic connections						
	Plant / Exhaust exchanger IN/OUT - ISO228/1-G M Ø	--	--	--	--	--	--
	Plant / Exhaust exchanger IN/OUT - OD (5)	Ø mm	88,9	88,9	88,9	88,9	88,9
	Partial heat recovery (6)						
	Heating capacity	kW	31,1	39,2	45,0	50,6	57,0
	Pumping group						
	Plant side - Power input	kW	--	--	--	--	--
	Source side - Power input	kW	--	--	--	--	--
	Water tank - volume	l	380	380	380	380	380

1. Referred to chilled water temperature 12/7°C – 0% glycol solution; water temperature to the condenser 30/35°C – 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.
2. Referred to hot water outlet temperature at 45°C and chilled water temperature 15/10°C - 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.
3. Sound power level [Lw] according to ISO EN 9614 - 2
4. Average sound pressure level [Lp_m] 1m far according to ISO EN 3744.
5. Hydraulic connection with grooved end complete with flexible joint and adapter pipe for solder connection.
6. Referred to chilled water temperature 12/7°C – 0% glycol solution; water temperature to the condenser 30/35°C – 0% glycol solution; water temperature heat recovery 40/45°C – 0% glycol solution. Fouling factor of the exchangers 0,043 m²K/kW.

(*)  Seasonal energy efficiency class according to energy label directive 2010/30/EU and EU regulations 811/2013.

DIMENSIONS (mm)

SIZE M	a	b	c
M1	785	725	1820
M2	1085	725	1820
M3	1480	935	1875
M4	2360	935	2025





for a greener tomorrow

Eco-Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.



MITSUBISHI ELECTRIC HYDRONICS & IT COOLING SYSTEMS S.p.A.

RC Brand: Via Roma 5 -27010 Valle Salimbene (PV) - Italy
Tel +39 (0) 382 433 811 - Fax +39 (0) 382 587 148

www.rcgroup.it
www.melcohit.com